PATENT ABSTRACTS OF JAPAN

(11) Publication number:

08-204288

(43) Date of publication of application: 09.08.1996

(51) Int. CI.

H01S 3/18 H01L 31/0232 H01L 33/00

(21) Application number: 07-007893

(71) Applicant: HITACH! LTD

(22)Date of filing:

23. 01. 1995 (72) Inventor: HIRATAKA TOSHINORI


KIKUCHI SATORU

(54) OPTICAL SEMICONDUCTOR DEVICE

(57) Abstract:

device in which an optical semiconductor element can be positioned with high accuracy without adjustment so as to improve the productivity of the device. CONSTITUTION: In an optical semiconductor device which is provided with a mounting substrate 3 on which an optical waveguide 2 is formed and an optical semiconductor element 1 which is mounted on the substrate 3 and is optically coupled with the waveguide 2 and a rear-ship surface electrode 6 provided on the rear surface of the element 1 and a metallic film 7 formed on the substrate 3 are fixed with solder bumps 8, a recessed groove 4 is formed on the surface of the substrate 3 at the position to which the optical semiconductor element is fixed. Therefore. the occurrence of such a phenomenon that the

PURPOSE: To provide an optical semiconductor



electrode pattern of the element 1 is not connected to an electrode pattern on the substrate 3 due to the positional deviation of the element 1 before melting solder is eliminated.

LEGAL STATUS

[Date of request for examination]

06.06.2000

[Date of sending the examiner's

21.01.2003

decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office